

UT380 series light meters measure light intensity and display results in Lux or Fc. It has a high sampling rate of 100/s. UT380 series 'low power consumption allows up to 200 hours of continuous operation. Results can be stored within the device and transferred to PC for further analysis, printing and storage.



UT382

| Specifications                | Range            | UT381   | UT382   |
|-------------------------------|------------------|---------|---------|
| <b>Certificates</b>           | <b>CE, UKCA</b>  |         |         |
| Illuminance measurement (Lux) | 20 Lux~20000 Lux | ±(3%+8) | ±(3%+8) |
| Illuminance measurement (Fc)  | 2 Fc~2000 Fc     | √       | √       |
| Display count                 |                  | 2000    | 2000    |
| Data storage                  |                  | 2044    | 2044    |
| USB interface                 |                  |         | √       |

| Features                 |                        |
|--------------------------|------------------------|
| Auto range               | MAX/MIN mode           |
| Auto power off/data hold | Auto record time setup |
| Low battery indication   | Real-time clock        |

| Characteristics              |                                 |
|------------------------------|---------------------------------|
| Standard accessories         | English manual                  |
| Power                        | 9V battery (6LF22)              |
| Display                      | 22.5 x 32.5mm                   |
| Product size                 | 195 x 45 x 26mm                 |
| Product net weight           | 185g                            |
| Standard individual packing  | Blister, gift box, Carrying bag |
| Standard quantity per carton | 10pcs                           |
| Standard carton measurement  | 445 x 320 x 180mm               |
| Standard carton gross weight | 3.4kg                           |